

Industrial Vacuum Cleaner



+91 9411787933



info@ekakshenterprises.com



The CleanTec Hi-Lo 15 has been designed from the ground up to reflect the need for quick and effective carpet care with the minimum of preparation and effort.

Within the single design we have incorporated our TwinFlo' high performance, carpet vacuum extraction system together with our dual, high performance, deep clean, PowerFlo' pump injection unit, providing a choice of two performance standards which can be selected at any time to suit your specific needs.

Almost every carpet cleaning task is made up of two specific areas:- the heavily soiled dirt tracked areas, always present in doorways and main walkways but, equally, a much larger area of carpet off the beaten track and only lightly soiled

The Hi-Lo system allows you to select the Hi pressure... 4 Bar (60 psi)... TriJet performance for heavily soiled areas and the Lo pressure... 2 Bar (30 psi) standard for lesser soiled areas. This system gives you the exact performance you need by simple selection, Hi or Lo, and reduces carpet wetting in areas where carpets need less cleaning penetration.

For user convenience we have allowed for two separate emptying systems: full removal of the dirty water tank or, where this is not practical, an integrated dump hose. Hi-Lo is not just for carpets, it has all the power, performance and convenience for the cleaning of fabrics and upholstery.



Easyflo System



High Efficiency Upholstery / Spotting Nozzle



Dump Hose Empty Option



Standard Accessories

Technical Specifications

Model No	Power	Motor	Airflow	Motor Power
NHL 15	230 V AC 50/60 Hz	2 x Twinflo	38 Ltrs/Sec	1200 W
Suction Lift	Capacity	Range	Weight	Dimensions (L x W x H)
2400 mm	15 Ltrs	26.8 m	15.5 Kgs	435 x 425 x 725 mm

